New



KU EDPU - 5.0 External Display Unit

Display suitable for

- MKU LO 8-13 PLL
- MKU LO 8-13 PLL-2
- MKU 76 G2 (together with MKU LO 8-13 PLL)
- MKU 10 G5
- MKU UP 2424 B

The 5-inch display unit from Kuhne electronic GmbH was developed to offer excellent picture quality and state-of-the-art functions in a robust housing. It is supported by many of our products.

Included supply

- Mini-DIN connection cable (1 meter)
- DC connection cable (2 meters)



Description

The 5-inch display unit from Kuhne electronic GmbH was developed to offer excellent picture quality and state-of-the-art functions in a robust housing. The display supports many our products and thus makes configuration/operation easier. Connecting the products is quick and easy thanks to the fixed plug-in system. We offer appropriate adapters as accessories for connecting the products.

Features

- Easy handling
- Automatic device detection
- Updatable
- Mounting holes on the back

Technical specifications:	
Screen Size (inch)	5 inch
Screen Resolution	800 x 400 pixel
Screen Type	IPS-touchscreen (capazitive)
Power Supply	10 14 V
power consumption	150 mA
Operating Temperatur	-20 +70 °C
Dimension (mm)	165 x 95 x 23 mm
Weight	408 g